

HCV2-RA, HCV4-RA, HCV8-RA REMOTE ANNUNCIATOR



DESCRIPTION

The 24VDC HCV series are available in a 2, 4, and 8 Zone designs. The remote annunciator is a single board construction, which is installer friendly.

The HCV series are compatible with any HCV series Conventional Panels which have operating software version V2.0 or above. Can connect up to 7 remote annunciators to any HCV series conventional panel using binary coded DIL switch.

The remote annunciator control input consists of Silence Alarm, Sound Alarm, Lamp Test and Reset. The board provides voltage free fire and fault contacts.

SPECIFICATIONS

Supply Voltage	24 VDC
Dimensions	385mm (W) x 310mm (H) x 60mm (D)
Weight	9 lbs.
Color	Red
Material	1.2mm mild steel
Wiring Length	1200 meters
Fault Contact Rating	30VDC 1 Amp
Fire Contact Rating	30VDC 1 Amp
Stand by Current	HCV2-RA: 0.075 Amp, HCV4-RA: 0.075 Amp, HCV8-RA: 0.094 Amp
Alarm Current	HCV2-RA: 0.094 Amp, HCV4-RA: 0.098 Amp, HCV8-RA: 0.11 Amp
Cable Capacity	2.5 mm per terminal
Operation Humidity	90% RH (Non-Condensing)
Operating Temperature	-5°C to 50°C

STANDARD FEATURES

- Fully compatible with HCV series conventional panels
- Up to 7 remote annunciators per system
- Full control over main panel remotely
- Voltage free fire and fault contact outputs
- Two wire serial connection

PRODUCT LISTING



KM 73505

Specifications subject to change without notice.

Continued on back.