

## Commercial Fire Alarm Cellular Communicators



### PRODUCT DESCRIPTION

**UL and NFPA 72 Fire Code-Compliant**, the StarLink Series Wireless Commercial Fire Alarm Sole Path & Dual Path Communicators provide universal support for any brand 12V to 24V fire alarm control panel, reporting in Contact ID and 4/2. With broadest Verizon LTE coverage footprint available, via most extensively deployed LTE CAT1, using proven StarLink circuitry, they are also available in mercantile locking metal models. All provide the most economical solution for easy, versatile installation. Also regional compliances, i.e., CSFM, NYCFD, LAFD and more.

**Easy, Universal Installation at Every Application; Panel Powered Technology™.** StarLink Fire Communications are easily connected to any panel or Fire Alarm Control Panel (FACP) standardly operating between 12V and 24V. Flexible in any application, StarLink Fire also comes in standard, or Mercantile Models in metal housings, with code-compliant supervision, and choice of power options, Panel-Powered Technology™ (powered by the panel), or direct-connect 120VAC models. Signal Boost circuitry & dual diversity antennae for maximum signal acquisition & null avoidance, receiving signals simultaneously on both antennae.

### STANDARD FEATURES

- Advanced LTE Dual Diversity Antennae for optimized performance
- Durable ABS plastic housing includes three keyhole slots for mounting (for commercial application, aligns with triple gang boxes)
- Panel Powered Technology™ (powered by panel), Low current draw, 71mA standby, 200mA transmit
- Dimensions: 5-3/8" x 7-7/8" x 1-7/8" (HxWxD)
- Weight: 13.5 oz
- 3 LED Indicators - Green, Signal Strength; Amber-Busy/ Activation; Red-Trouble
- Patented Signal Boost™ signal amplification circuit and highgain performance antennae
- Operating Environment: 0 to 49° C (32-120°F), up to 93% humidity (non-condensing)
- 12V - 24V Universal FACP Support, auto-current sensing. Support all brands communicating in Contact ID and 4/2

**Flexible Performance & Reporting Options.** StarLink Fire provides full data reporting, in sole and dual path, as a primary or backup, to any central station of your choice, without requiring any special equipment on premises. Ultra-affordable plans are available to meet various codes and requirements, with supervisory check-ins from 200 seconds, to 5 minutes, to an hour. The units are very easily activated, plans and options are selected, and 24/7 account management is provided all through [www.napcocomnet.com](http://www.napcocomnet.com).

### ACCESSORIES

**Free Commercial Fire Tradeup Trifold Brochures / Mailers/ Stuffers (A720)** for new and existing fire accounts

**SLE-ANEXT75** Optional extended antenna with 75' cable (new conical shape)

**SLE-ANEXT50** As above, with 50' cable

**SLE-ANEXT30** As above, with 30' cable

**SLE-DLEXT** Optional, as above, for downloading, extends distance to Napco panel up to 100'

**TRF12** Optional Plug in AC Transformer, 16.5V / 20VA (use is subject to local code compliance)

**SLE-DLCBL** Optional High-Speed Napco Panel Up/download cable

### PRODUCT LISTINGS



Certified

*Specifications subject to change without notice.*